

Ideal for use in shopping malls, retail outlets, and institutional facilities



*Staying Three Steps Ahead
Of The Competition.*

Step Into The Future of Entryway Design.

Design-Links 2 is widely considered the industry's most innovative entryway. Design Links 2, with replaceable velcro carpet strips, combines our unique open-weave, grid-rib design with 1 3/16" wide carpet strips, creating a system that removes and contains dirt while drying wet shoes at the same time.

The patented system is designed to eliminate the rattling and clanking noises associated with similar products. The carpet strips, while providing an attractive, finished look, are held in place with hook and loop fasteners and can be easily removed for color coordinating or replacement when worn out.



Design-Links 2 Systems, Flooring, and Matting feature easy-to-replace, velcro-mounted carpet strips.

Design-Links 2 helps ensure a quieter, safer, cleaner interior while maintaining the desired aesthetics. No matter what your individual preference or needs may be, Design-Links 2 offers an entryway to compliment your facility's requirements.

See our three entryway options below.



Design-Links 2 System™

Combines the open-weave, grid-rib design of Power-Links, with easy-to-replace, velcro-attached carpet strips. Reflects an upscale look that provides both scraping and wiping action as well as containment. Includes Design-Links 2 vinyl quads, aluminum perimeter frame, internal grid frame and mat retainers.



Design-Links 2 SE™ Flooring

Provides the illusion of a seamless floor with the versatility and the ease of maintenance of a modular floor. Includes Design-Links 2 vinyl quads with easy-to-replace, velcro-attached carpet strips and mat retainers. Optional aluminum perimeter framing is available.



Design-Links 2 VR™ Matting

Offers the performance of a system, but in a loose-lay form with vinyl ramps. Design-Links 2 VR has easy-to-replace, velcro-attached carpet strips and a perimeter of vinyl ramp. Optional mat retainers are available to hold the mat in place.



Designed To Be The Best

Toll-Free: 800-233-4575 • Phone: 330-788-2401
Fax: 330-788-9665 • Web: www.spacelinks1.com



DESIGN-LINKS 2™ PRODUCT SPECIFICATIONS

PRODUCT IN PLACE

Design-Links 2 can be made to any width or length specifications. Individual quads will be customized in size to meet overall dimensions. Quads are held in place from underneath with snap fit mat retainers.

Design-Links 2 can be surface-mounted or recessed into the floor with optional frame. The mat is approximately .5" high and is surrounded by optional anodized aluminum ramps (where surface mounted) and optional dividers (where recessed). For recessed applications, well should be .5" deep. In all cases, the mounting surface should be a hard, smooth surface. Please call for CAD details.

MATERIALS AND FINISHES

The Design-Links 2 flooring consists of flexible, injection-molded, 100% virgin PVC quads that can be surrounded by optional .75" x .5", 1-3/8" overlapping divider, anodized aluminum frames and 2" x .5" anodized aluminum ramps. Our anodized frames are available in a satin finish in Clear, Black, Bronze and Gold. The surface of the mat features removable carpet strips, placed every 1.25", and held in place with hook and loop fasteners. Each mat is custom-engineered to fit the application. Standard colors for vinyl include Hunter Green, Chocolate Brown and Black. Standard colors for removable carpet strips are Charcoal, Forest Green and Walnut. Custom color combinations are available in vinyl, fiber, dividers and ramps. We can also bend frames and ramps to a specified radius. Also available are transitional 3/8" to 1/2" dividers and overlapping dividers.

TECHNICAL SUPPORT

Test Results - Properties and Standards

Please call our Customer Service Department for additional information.

VINYL PROPERTIES	
Thickness	5/8"
Hardness, Shore 'A', ASTM D 2240-86	85
Specific Gravity, STM D 792	1.34
Tensile Strength, ASTM D 412, Die C	2640 psi
Elongation % at Break, ASTM D 412 Die C	365 psi
100% Modulus, ASTM 412 Die C	1339 psi
Tear Strength, ASTM D 624	362 psi
Low Temperature Brittleness, ASTM D 11	-37° C
Static Coefficient of Friction, ASTM D 2047	Dry Leather = .79 Wet Leather = 1.04 Values greater than .5 are considered slip-resistant

ALUMINUM PROPERTIES	
Optional Aluminum Frame Composition	6063 - T5
Lineals, Dividers and Ramps	Outdoor, all-weather anodized aluminum
Colors Available	Clear, Black, Bronze, Gold

FIBER PROPERTIES	
2.05 Carpet Insert Options	Carpet shall be Meka Brush Super utilizing engineered Dartex fiber in dense cut pile construction, to maximize scraping action, crush resistance and soil retention. For interior applications only.
Face Weight	26 oz. Sq.Yard
Denier	2750
Fiber	Engineered 100% polypropylene blends
Backing	Vinyl and hook and loop fastening system.
Carpet Insert Colors	Charcoal, Walnut, Forest Green

SPACE-LINKS are covered by these Patent Numbers: 4,796,399 / 5,882,764 / 5,958,538 / 5,992,105 / 6,042,915 / 6,068,908
Other domestic and international patents pending.



Designed To Be The Best

Toll-Free: 800-233-4575 • Phone: 330-788-2401
Fax: 330-788-9665 • Web: www.spacelinks1.com